



Compact Charging For Up To 8 Handhelds

Portsmith's PSD Series multi-slot desktop charger provides continuous charging in a small form factor. Configurations include 2-slot, 4-slot, 6-slot, and 8-slot. Compatible with Zebra TC2X, TC5X, and TC7X as well as Honeywell CT Series and EDA Series.



Reliable Power

- Always on power and charging
- On-board over-power protection
- LED status indicator for each slot

Built For Enterprise

- Rugged ABS cradle elements
- Steel chassis structure
- Portsmith's renowned quality
- 1-year warranty

Specifications

- 2, 4, 6, and 8 slot configurations
- Power supply included
- One-hand insertion / removal
- For sale in US and Canada

Contact Jeff Moeser
Phone 1.208.888.5813 x 1010
E-mail sales@portsmith.com

PSD Series Cradle Cleaning Procedure

1. Remove the power cable from the cradle.
2. Dip a cotton-tipped applicator in isopropyl alcohol.
3. Gently rub the moistened cotton-tipped applicator along the pins of the connector. Slowly move the applicator back and forth from one side of the connector to the other.
4. Rub all sides of the connector with the cotton-tipped applicator
5. Spray compressed air in the connector and point the tube/nozzle about ½ inch away from the surface.
6. If grease or other type or other debris are found on the other areas of the cradle use a lint free cloth and spray isopropyl alcohol or a pre-moistened alcohol cloth to remove
7. Inspect and remove any residual (e.g. cotton, cloth, etc.) that may have attached to the connector during the cleaning process
8. Allow the isopropyl alcohol to air dry and dry with as soft lint-free cloth or towelette.
9. To clean the cradle body use a lint-free cloth to apply isopropyl alcohol over the surfaces of the cradle body. Gently rub the surfaces with the cloth.
10. Ensure electrical contacts and cradle body are fully dry before applying power.

Specifications and Dimensions

	2-slot	4-slot	6-slot	8-slot
Length	3.5-in/90mm	6.5-in/165mm	9.4-in/240mm	12.2-in/310mm
Width	5-in/125mm	5-in/125mm	5-in/125mm	5-in/125mm
Height	2.1-in/55mm	2.1-in/55mm	2.1-in/55mm	2.1-in/55mm
Weight	1-lb/445g	1.75-lb/795g	2.4-lb/1015g	2.8-lb/1295g

Input Pwr	12V2A	12V2A	12V2A	12V2A
Output Pwr / slot	5VDC1A	5VDC1A	5VDC1A	5VDC1A
Charging time	Typically, 1-3 hours depending on battery charge status and hand-held			

Approvals	US/CAN/CE/UK
------------------	--------------